

# NBP2100H Tech Sheet

**Customer:** NanTong

**Part Number:** 56749 800 Incoloy 3kW

Custom Box Overlay

Box Overlay Part Number N/A

CE System Model: BP21-NBP2100H-RCA3.0K

Software Version ID: M100\_225 V27.0

Software Version: 27.0

File Name: BP2100\_27.0\_NBP2100H\_SW.hex

Configuration Signature: 09D86769

Eng. Project Number: 4459

Control Panels:

TP800 version 3.1\* or later (Version 3.13 or later required for bba™)

\* TP800 version 4.2 or later (or spaTouch™ version 2.2 or later) required for new reminders to display correctly.



Manufactured under one or more of these patents. U.S. Patents: 5332944, 5361215, 5550753, 5559720, 5,883,459, 6253227, 6282370, 6590188, 6976052, 6965815, 7030343, 7,417,834 b2, Canadian Patent: 2342614, Australian patent: 2373248 other patents both foreign and domestic applied for and pending. © Copyright 2012 Balboa Water Group.

# System Revision History

Part #	EPN	Date	Originator	Changes Made
ZT000084	4248	04-10-14	BWG	New generic BP2100 with 4 Pumps plus optional blower and/or Circ.
56625, 56626, 56627	4248	05-01-14	BWG	Released to production.
ZT000147	4459	03-02-15	Customer	Custom BP2100 system with heater on its own service (except in 4-pump setups).
56749	4459	04-08-15	Customer	Approved for production.

bba™ (Balboa Bluetooth Amp) connection is documented separately.

bba™ is only integrated into graphic display panels (TP800, TP900 and spaTouch™). With TP600 the Aux button operation of bba™ must be used.

# Basic Functions Setup 1-8

---

## Power Requirements:

**Single Service** [3 wires (line, neutral, ground)] – RESTRICTED OPERATIONS (See page 5)  
230VAC, 50/60Hz\*, 1p, 32A, (Circuit Breaker rating = 40A max.)

**Dual Service** N/A

**3-Service** [5 wires (line 1, line 2, line 3, neutral, ground)]  
400VAC, 50/60Hz\*, 3p, 16A, (Circuit Breaker rating = 20A max each phase line.)

**IMPORTANT** - Service must include a neutral wire, with a line to neutral voltage of 230VAC.

\*BP systems automatically detect 50Hz vs 60Hz.

---

### HiPot Testing Note:

Disconnect slip terminal with green wires from J11 prior to performing HiPot test. Failure to disconnect may cause a false failure of the test. Reconnect terminal to J11 after successful completion of HiPot test.

## In 3x16A Service:

Pump 2 and Pump 3 (if any) are on one service.

Pump 4 and the heater are on another service.

Everything else is on the remaining service. (Note: When using Blower, wiring must be changed for Blower to not be on the heater service.)

# Basic Functions Setup 1-8

## System Outputs:

Pump 1	230VAC	2-Speed 1-Speed in Setups 5-8	10A max	15-minute timer for High Speed, 15-Minute timer for Low Speed
		This is the heater pump in Setups 1-4 Must deliver 20 GPM through heater		
Pump 2	230VAC	1-Speed	8A max**	15-minute timer
Pump 3	230VAC	1-Speed	8A max	15-minute timer Unused in Setups 4, 8, 9 & 10
Pump 4	230VAC	1-Speed	10A max	15-minute timer Used in Setups 1, 5, 9 & 10 only
Blower	230VAC	1 Speed	4A max	15-minute timer Unused in Setups 1, 2, 5, 6, 9 & 10
Circ Pump	230VAC	1-Speed	2A max	Programmable Filtration Cycles + Polling This is the heater pump in Setups 5-8 Must deliver 20 GPM through heater
Ozone	230VAC		.5A max	Slaved to Circ Pump in Setups 5-8 Independent in Setups 1-4, 9 & 10
Spa Light	10VAC	On/Off	1A max	240-minute timer.
A/V (Stereo)	230VAC	Hot	2A max*	Always on
Heater	3.0kW @ 240VAC max			

In Setups 9 & 10 *only*: Pumps 1, 2 & 4 can be 12A max each.

\* See restrictions on next page.

\*\* When there is no Pump 3 (ie. in Setups 4 & 8 only), Pump 2 can be 10A max.

# Basic Functions Setup 1-8

---

## Restrictions:

In 3x16A, all equipment (if within the individual maximums listed on page 4) can run together, except the heater turns off with any high-speed pump or blower, when running 4 pumps (Setup 1 or Setup 5). (DIP switch A5 must be OFF.)

In 1x32A, DIP switch A5 must be ON. With DIP Switch A5 ON, only 3 pumps (any 3 pumps) can be ON at high speed at any one time, and the blower will not run when 3 pumps are ON at high speed.

In 1x40A, with DIP switch A5 ON, it works just like at 1x32A.


To be able to use 1x40A with DIP switch A5 OFF (ie, no restrictions except for the heater), all the 230V equipment used in the spa (except for the heater) must add up to no more than 39.5 Amps. This means all pumps, the blower (if any), the circ pump (if any), the ozone, and A/V (if any). (There is 0.5 Amps at 230V reserved for board and panel power as well as 10V equipment including the spa lights. That is why the 230V equipment must add up to 39.5 Amps rather than 40.0 Amps.)

## See this chart for some 1x40A examples:

Pump 1	10A	10A
Pump 2	8A	8A
Pump 3	8A	8A
Pump 4	10A	None
Blower	None	4A
Circ	2A	2A
Ozone	0.5A	0.5A
A/V	None	2A
Total	38.5A	34.5A
Will it work?	Yes	Yes

# Hardware Setup

## Wiring Diagram



PART A

# Hardware Setup

## Settings

SINGLE SERVICE 230V 1p / 1x32A, THREE-SERVICE 230V 1p / 3x16A

LOCATION	DEVICE
J9	NETZSTROMVERSORGUNG 2/1-GESCHW.-PUMPE 1 ALIMENTATION POMPE 1 A 2/1 VITESSES 2/1-SPEED PUMP 1
J14	NETZSTROMVERSORGUNG 2/1-GESCHW.-PUMPE 2 ALIMENTATION POMPE 2 A 2/1 VITESSES 2/1-SPEED PUMP 2 + NETZSTROMVERSORGUNG 2/1-GESCHW.-PUMPE 3 ALIMENTATION POMPE 3 A 2/1 VITESSES 2/1-SPEED PUMP 3 P2 + P3 LINE 1 CONNECTION J19 to J43
J15	10V BELEUCHTUNG ECLAIRAGE BAIN HYDRO SPA LIGHT
J21	KREISLAUF PUMPE POMPE DE CIRCULATION CIRC PUMP (SETUPS 5-8)
J32	OZONGENERATOR GENERATOROZONE OZONE GENERATOR CIRC AND OZONE LINE 1 CONNECTION J81 to J59
J33	TV / AV
J40	IR RECIEVER
J5, J8	AUX PANEL(S) - AX10, AX20, AX30, AX40



SETUP # CIRC PUMP PUMP 1 PUMP 2 PUMP 3 PUMP 4 BLOWER MENU STYLE TEMP SCALE

SETUP #	CIRC PUMP	PUMP 1	PUMP 2	PUMP 3	PUMP 4	BLOWER	MENU STYLE	TEMP SCALE
1	NONE	2-SPEED	1-SPEED	1-SPEED	1-SPEED	NONE	STANDARD	°C
2	NONE	2-SPEED	1-SPEED	1-SPEED	NONE	NONE	STANDARD	°C
3	NONE	2-SPEED	1-SPEED	1-SPEED	NONE	1-SPEED	STANDARD	°C
4	NONE	2-SPEED	1-SPEED	NONE	NONE	1-SPEED	STANDARD	°C
5	PROGRAMMABLE FILTRATION + POLLING	1-SPEED	1-SPEED	1-SPEED	1-SPEED	NONE	STANDARD	°C
6	PROGRAMMABLE FILTRATION + POLLING	1-SPEED	1-SPEED	1-SPEED	NONE	NONE	STANDARD	°C
7	PROGRAMMABLE FILTRATION + POLLING	1-SPEED	1-SPEED	1-SPEED	NONE	1-SPEED	STANDARD	°C
8	PROGRAMMABLE FILTRATION + POLLING	1-SPEED	1-SPEED	NONE	NONE	1-SPEED	STANDARD	°C
9	NONE	2-SPEED	1-SPEED	NONE	1-SPEED	NONE	STANDARD	°C
10	NONE	2-SPEED	1-SPEED	NONE	1-SPEED	NONE	SIMPLE	°C

230V 1p 1x32A	SWITCHBANK S1 OFF	SWITCHBANK S1 ON
	TEST MODE OFF	TEST MODE ON
	DON'T ADD 1 HS PUMP W/HTR	ADD 1 HS PUMP WITH HEAT
	DON'T ADD 2 HS PUMPS W/HTR	ADD 2 HS PUMPS WITH HEAT
	DON'T ADD 4 HS PUMPS W/HTR	ADD 4 HS PUMPS WITH HEAT
	SPECIAL AMPERAGE RULE A	SPECIAL AMPERAGE RULE B
	STORE SETTINGS*	MEMORY RESET*
	1 MIN HTR COOLDOWN (ELEC)	5 MIN HTR COOLDOWN (GAS)
	NOT ASSIGNED	NOT ASSIGNED
	NOT ASSIGNED	NOT ASSIGNED
	NOT ASSIGNED	NOT ASSIGNED

\*SWITCH # 6 SHOULD BE SET TO OFF UPON FINAL INSTALLATION.

INSTEAD OF SETUP #8,  
THIS SYSTEM IS  
CONFIGURED IN  
SETUP #:



PUMPS 1, 2 & 4  
CAN BE 12A MAX IN  
SETUPS 9 & 10 ONLY

04-14-15 **BALBOA**  
NBP2100H - PN 56749 water group

FOR SUPPLY CONNECTIONS,  
USE CONDUCTORS SIZED ON THE  
BASIS OF 60°C AMPACITY BUT  
RATED MINIMUM OF 90°C.

USE COPPER CONDUCTORS ONLY.  
EMPLOYER UNIQUEMENT  
DES CONDUCTEURS DE CUIVRE.

TORQUE RANGE FOR  
MAIN TERMINAL BLOCK (TB1):  
27-30 IN. LBS.  
(31.1-34.5 kg cm)

PART B

# Setup Reference Table

Setup #	Circ Pump	Pump 1	Pump 2	Pump 3	Pump 4	Blower	Menu Style	Temp Scale
1	None	2-Speed	1-Speed	1-Speed	1-Speed	None	Standard	°C
2	None	2-Speed	1-Speed	1-Speed	None	None	Standard	°C
3	None	2-Speed	1-Speed	1-Speed	None	1-Speed	Standard	°C
4	None	2-Speed	1-Speed	None	None	1-Speed	Standard	°C
5	Programmable Filtration + Polling	1-Speed	1-Speed	1-Speed	1-Speed	None	Standard	°C
6	Programmable Filtration + Polling	1-Speed	1-Speed	1-Speed	None	None	Standard	°C
7	Programmable Filtration + Polling	1-Speed	1-Speed	1-Speed	None	1-Speed	Standard	°C
8	Programmable Filtration + Polling	1-Speed	1-Speed	None	None	1-Speed	Standard	°C
9	None	2-Speed	1-Speed	None	1-Speed	None	Standard	°C
10	None	2-Speed	1-Speed	None	1-Speed	None	Simple	°C

**System** (and any replacement board) **is shipped in Setup 8**

Color Key	Output
	XP231
	XP231 and in-line Blower fuse
	J14 (Aux) on Main Board




# Changing Software Setups with TP800 / TP900 / spaTouch™ Menued Panel

## Test Menu Access (S1, Switch 1 ON) *Service Technician ONLY.*


**DANGER! HIGH VOLTAGE WILL BE ACCESSIBLE! SERVICE TECHNICIAN ONLY!**

While the system is running, move DIP Switch 1 (on S1 on the Main circuit board) to ON.  
The system will enter Test Mode.  
Moving DIP Switch 1 to OFF will exit Test Mode.



## Software Setups

Under the TEST Menu, the Setup screen will allow changing the Setup from 1 to any number established by the Manufacturer.  
Changing the Setup may require wiring changes as well.



Note: The Timeouts and Temp Limit selections should NEVER be changed. They are for safety agency testing purposes only.

# Equipment Expansion

---

## Expansion Features


### Control Connection

	<b>Default</b>	<b>Fuse</b>
Relay 1 (J101)	Undefined	None
Relay 7/8 (J107)	See Below 1-Speed Pump 4 OR 1-Speed Blower (with Fused Adapter)	30A
Relay 9/10 (J108)	Undefined	None

# DIP Switch Functions

## Fixed-function DIP Switches

- A1 Test Mode (normally Off).
- A2 In "ON" position, add one high-speed pump (or blower) with Heater.
- A3 In "ON" position, add two high-speed pumps (or 1 HS Pump and Blower) with Heater.
- A4 In "ON" position, add four high-speed pumps (or 3 HS Pumps and Blower) with Heater.
- A5 In "ON" position, enables Special Amperage Rule B. See Special Features section under Configuration Options for functionality with your system.  
In "OFF" position, enables Special Amperage Rule A.
- A6 Persistent memory reset (Used when the spa is powering up to restore factory settings as determined by software configuration).



**A2, A3, and A4** work in combination to determine the number of high-speed devices and blowers that can run before the heat is disabled. i.e. A2 and A3 in the ON position and A4 in the OFF position will allow the heater to operate with up to 3 high-speed pumps (or two HS Pumps and Blower) running at the same time. Heat is disabled when the fourth high-speed pump or blower is turned on.










**Note:** A2/A3/A4 all off = No heat with any high-speed pump or blower.

## Assignable DIP Switches

- A7 In "ON" position, enables a 5-minute cooldown for some gas heaters (Cooling Time B).  
In "OFF" position, enables a 1-minute cooldown for electric heaters (Cooling Time A).

*Undesignated switches are not assigned a function.*

# Jumper Definitions

<b>J109</b>	Non Applicable on CE models	J109 
<b>J91</b>	Real Time Clock Enable/Disable <b>Note:</b> This Jumper should NOT be shorted when the Control Panel can display time of day.	J91 
<b>J30</b>	Do Not Use	
<b>J31</b>	Jumper on 1 pin with 2.0kW or smaller heater Jumper on 2 pins with a 3.0kW or higher heater	J31 
<b>J29</b>	Heater Disable Switch Connection. If J29 is shorted by any means, the heater will not run until J29 is no longer shorted. If J29 is shorted during power-up “J29” will appear on the panel. The message can be dismissed with a button press, and is the only control panel notification of J29 being shorted. No message is displayed if J29 is shorted after power-up, but the heater will not run until J29 is no longer shorted. J29 expects a switch closure (not a voltage) as the command signal. In some areas, a local power company may offer discounts based on voluntary “power shedding” devices that may be installed in conjunction with the spa.	J29 
<b>J25, J26, J27</b>	Heater Type Settings. <b>Note:</b> Factory Configured do not change.	J25  J26  J27 
<b>J24</b>	Jumper on center two pins (230V) when heater is running at 240V. Two Jumpers installed; one on left 2 pins and one on right 2 pins (115V) when heater is running at 120V.	J24  230V 115V  115V

## Warning!

Setting DIP switches or jumpers incorrectly may cause abnormal system behavior and/or damage to system components. Refer to Switchbank illustration on Wiring Configuration page for correct settings for this system. Contact Balboa if you require additional configuration pages added to this tech sheet.

# Replacement Parts

---

## PCBA:

Main PCBA: 56750  
Expander PCBA: 55137

## HEATER(s):

Plug + Click Heater Kit: 58300  
Temp Sensor: 30344

## CABLES:

25739 Y-Adapter P2+P3  
25681 Adapter Blower

## FUSES:

Part Number	Amperage	Location
30136	30A	F6, F8, F1 (Expander)
20600	3A	F4
26397	1/8A	F3
30122	10A	F2, F7

# BP2100 Configuration Options

---

## General Features

Feature	Default
Pump 1 in Filter Cycle (Circ Only)	No
Pump 1 Low Timer	30 Minutes
General Pump Timer	15 Minutes
Blower Timer	15 Minutes
Mister Timer	15 Minutes
Light Timer	240 Minutes
Circ (when enabled)	Programmable + Polling
Cleanup Cycle	<i>30 Minutes</i>
Cleanup as Preference setting	<i>Yes</i>
Ozone	With Heater Pump*
Ozone Suppression	OFF
Pump Purge	60 Seconds
Blower Purge	30 Seconds
Mister Purge	5 Seconds
Purge Type	Serial - Pumps at lowest speed

\* The heater Pump can be either a Circ Pump or Pump 1 Low.

Manufactured under one or more of these patents. U.S. Patents: 5332944, 5361215, 5550753, 5559720, 5,883,459, 6253227, 6282370, 6590188, 6976052, 6965815, 7030343, 7,417,834 b2, Canadian Patent: 2342614, Australian patent: 2373248 other patents both foreign and domestic applied for and pending. © Copyright 2012 Balboa Water Group.

# BP2100 Configuration Options

## Temperature Features

Feature	Default
Temperature Display	°C

All temperatures must be specified in °F. The system converts °F to °C dynamically. If Celsius is required for default settings, choose a desired °C value that (after rounding) corresponds to a Fahrenheit value.

°C	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
°F	39	41	43	45	46	48	50	52	54	55	57	59	61	63	64	66	68	70	72
°C	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	
°F	73	75	77	79	81	82	84	86	88	90	91	93	95	97	99	100	102	104	

Hi-Range Min. Set Temp	80°F
Hi-Range Max. Set Temp	104°F
Hi-Range Default Temp*	100°F
Lo-Range Min. Set Temp	50°F
Lo-Range Max. Set Temp	99°F
Lo-Range Default Temp*	70°F
Freeze Threshold	44°F
Freeze Type	Rotating - Pumps at Lowest Speed
Temp Lock Type	Temp + Settings

\*May be changed by end-user (if enabled)

Manufactured under one or more of these patents. U.S. Patents: 5332944, 5361215, 5550753, 5559720, 5,883,459, 6253227, 6282370, 6590188, 6976052, 6965815, 7030343, 7,417,834 b2, Canadian Patent: 2342614, Australian patent: 2373248 other patents both foreign and domestic applied for and pending. © Copyright 2012 Balboa Water Group.

# BP2100 Configuration Options

---

## Time Features

Feature	Default
Time Format*	24 Hour
Filter 1 Start Hour*	20:00 (8:00 PM)
Filter 1 Duration*	2 Hours
Filter Cycle 2 Default*	OFF
Filter 2 Start Hour*	08:00 (8:00 AM)
Filter 2 Duration*	15 Minutes
Light Cycle	Disabled
Light Cycle Default*	OFF
Light Cycle Start Hour*	21:00 (9:00 PM)
Light Cycle Duration*	15 Minutes
Cooling Time A	1 Minute
Cooling Time B	5 Minutes

*\*May be changed by end-user (if enabled)*

Manufactured under one or more of these patents. U.S. Patents: 5332944, 5361215, 5550753, 5559720, 5,883,459, 6253227, 6282370, 6590188, 6976052, 6965815, 7030343, 7,417,834 b2, Canadian Patent: 2342614, Australian patent: 2373248 other patents both foreign and domestic applied for and pending. © Copyright 2012 Balboa Water Group.



# BP2100 Configuration Options

---

## Reminder Features

Feature	Default
Reminders Shown*	Yes
Check pH	7 Days
Check Sanitizer	7 Days
Clean Filter	7 Days
Test GFCI	60 Days
Drain Water	90 Days
Change Cartridge	OFF
Clean Cover	90 Days
Treat Wood	OFF
Change Filter	120 Days
Check Ozone (E047**)	365 Days
Service Check-up (E048**)	240 Days

*\*\* On TP panels that have not been updated to display these new reminders, they will display as these numeric codes.*

*\*May be changed by end-user (if enabled)*

Manufactured under one or more of these patents. U.S. Patents: 5332944, 5361215, 5550753, 5559720, 5,883,459, 6253227, 6282370, 6590188, 6976052, 6965815, 7030343, 7,417,834 b2, Canadian Patent: 2342614, Australian patent: 2373248 other patents both foreign and domestic applied for and pending. © Copyright 2012 Balboa Water Group.

# BP2100 Configuration Options

---

## Special Features

### Feature

### Default

Special Amperage Rule A

No Limitation

Special Amperage Rule B

3 high-speed pumps max. Blower turns off with 3 high speed pumps

Drain Mode

Disabled

Demo Mode

Disabled

GFCI Trip

Not Applicable for CE Models

Ozone Slaved to Heater Pump

*Yes in circ setups*  
*No in non-circ setups*

Dual Voltage Heater

Always Input Voltage

Safety Suction

Disabled

Menu Style

*Standard in Setups 1 - 9*  
*Simple in Setup 10*

# TP800 Panel Configuration




**Button Layout Table**

Feature #	4 Pumps & Circ Setup 5	4 Pumps & No Circ Setup 1	NO Blower & Jets 3 Setup 2	Blower & Jets 3 Setup 3	Blower & NO Jets 3 Setup 4	NO Blower & Jets 3 & Circ Setup 6	Blower & Jets 3 & Circ Setup 7	Blower & NO Jets 3 & Circ Setup 8	Pumps 1, 2 & 4, NO Circ Setup 9
A1	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
A2	Jets 1	Jets 1	Jets 1	Jets 1	Jets 1	Jets 1	Jets 1	Jets 1	Jets 1
A3	Jets 2	Jets 2	Jets 2	Jets 2	Jets 2	Jets 2	Jets 2	Jets 2	Jets 2
A4	Jets 3	Jets 3	Jets 3	Jets 3	Blower	Jets 3	Jets 3	Blower	Jets 4
A5	Jets 4	Jets 4	Light 1	Blower	Light 1	Light 1	Blower	Light 1	Light 1
A6	Light 1	Light 1	Invert	Light 1	Invert	Invert	Light 1	Invert	Invert
A7	Invert	Invert	Undefined	Invert	Undefined	Undefined	Invert	(Circ Icon)	Undefined
A8	(Circ Icon)	Undefined	Undefined	Undefined	Undefined	Undefined	(Circ Icon)	Undefined	Undefined
A9	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined
A10	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined
A11	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
A12	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
A13	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined
A14	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined
A15	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined
A16	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined	Undefined
B1	Jets 1	Jets 1	Jets 1	Jets 1	Jets 1	Jets 1	Jets 1	Jets 1	Jets 1
B2	Jets 2	Jets 2	Jets 2	Jets 2	Jets 2	Jets 2	Jets 2	Jets 2	Jets 2
B3	Jets 3	Jets 3	Jets 3	Jets 3	Blower	Jets 3	Jets 3	Blower	Jets 4
B4	Jets 4	Jets 4	Light 1	Blower	Light 1	Light 1	Blower	Light 1	Light 1




TP800 is not supported in Simplified Menu Setup 10.

# TP800 Panel Configuration

## Spa Screen



## Shortcuts Screen



**Note:** Buttons 11 and 12 are not used in this configuration.  
Button 1 is fixed.

*A Circ Icon will appear when a Circ Pump is configured.*

# TP600 Panel Configuration

## Button Layout Table

Button #	Setups 9 & 10
1	Jets 1
2	Jets 2
3	Jets 3
4	Up
5	Light 1
6	Down
LED 1	Jets 1
LED 2	Jets 2
LED 3	Light 1
LED 4	Heat On

TP600 is not supported in Setups 1 - 8.



### TP600CE

50015-XX

No Overaly

# BP2100 Configuration Options

---

## Auxilliary Panel Features on Bank 1\*

Feature	Default
Aux Button A1	Jets 1
Aux Button A2	Jets 2
Aux Button A3	Blower
Aux Button A4	Light

## Auxilliary Panel Features on Bank 2\*

Feature	Setups 1, 5, 9 & 10	Setups 2 & 6	Setups 3 & 7	Setups 4 & 8
Aux Button A5	Jets 1	Jets 1	Jets 1	Jets 1
Aux Button A6	Jets 2	Jets 2	Jets 2	Jets 2
Aux Button A7	Jets 3	Jets 3	Jets 3	Blower
Aux Button A8	Jets 4	Light	Blower	Light

Buttons that are assigned to equipment that is not defined in a Setup will not do anything in that Setup.


\*Bank 1 consists of J5 on the Main Circuit Board.  
 Bank 2 consists of J8 on the Main Circuit Board.  
**Aux Connection Splitter PN25257 may be required.**

# BP2100 Configuration Options

## Auxilliary Panel Features

### AX10 Panels on Bank 1\*

A1, AX10A1	No O/L	52803
A2, AX10A2	No O/L	52804
A3, AX10A3	No O/L	52805
A4, AX10A4	No O/L	52806



Call Customer Service for additional information about Auxiliary Panels.


### AX10 Panels on Bank 2\*

A5, AX10A1	No O/L	52803
A6, AX10A2	No O/L	52804
A7, AX10A3	No O/L	52805
A8, AX10A4	No O/L	52806

\*Bank 1 consists of J5 on the Main Circuit Board.  
Bank 2 consists of J8 on the Main Circuit Board.  
**Aux Connection Splitter PN25257 may be required.**

### AX20


AX20 A1A2	No O/L	52800
AX20 A1A3	No O/L	52801
AX20 A1A4	No O/L	52802



**AX20 Auxiliary Panel plugged into Bank 1 will operate A1 + A2, A3 or A4.**  
**AX20 Auxiliary Panel plugged into Bank 2 will operate A5 + A6, A7 or A8.**

### AX40

AX40	No O/L	52799
------	--------	-------




**AX40 Auxiliary Panel plugged into Bank 1 will operate A1 + A2, A3 and A4.**  
**AX40 Auxiliary Panel plugged into Bank 2 will operate A5 + A6, A7 and A8.**

# BP2100 Configuration Options

## Remote Panel Features

Feature	Setups 1, 5, 9 & 10	Setups 2 & 6	Setups 3 & 7	Setups 4 & 8
Remote Button A1	Jets 1	Jets 1	Jets 1	Jets 1
Remote Button A2	Jets 2	Jets 2	Jets 2	Jets 2
Remote Button A4	Jets 3	Jets 3	Jets 3	Blower
Remote Button A5	Jets 4	Light	Blower	Light



Remote buttons A3, A6, A7 and A8 are Undefined.

Buttons that are assigned to equipment that is not defined in a Setup will not do anything in that Setup.

Remote Panel Part Number \_\_\_\_\_  
 Overlay Part Number \_\_\_\_\_

Manufactured under one or more of these patents. U.S. Patents: 5332944, 5361215, 5550753, 5559720, 5,883,459, 6253227, 6282370, 6590188, 6976052, 6965815, 7030343, 7,417,834 b2, Canadian Patent: 2342614, Australian patent: 2373248 other patents both foreign and domestic applied for and pending. © Copyright 2012 Balboa Water Group.

